

[View Product](#)

|                      |                                                  |
|----------------------|--------------------------------------------------|
| SKU                  | 259002                                           |
| EAN                  | 8719157076814                                    |
| Manufacturer Code    | 8719157076814                                    |
| Brand                | Ledvance                                         |
| Manufacturer Name    | Multipack 6x DL SLIM DN105 6W/4000K WT IP20 LEDV |
| Budgetlight warranty | 3 Years                                          |
| Average Lifetime (h) | 30000                                            |

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tilttable                   | No                |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 1x18              |
| Wattage                     | 6W                |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 840 Cool White    |
| Colour temperature (Kelvin) | 4000 Cool White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |

|                       |                                       |
|-----------------------|---------------------------------------|
| Light colour options  | Single Color                          |
| Beam Angle (degree)   | 120                                   |
| Luminous Flux (Lumen) | 430lm                                 |
| Lumen per watt        | 70                                    |
| Power factor          | >0.50                                 |
| Unified Glare Rating  | < 28 - for hallways and storage rooms |
| Optical Cover         | PC (Polycarbonate)                    |
| Product Type Category | LED Downlight                         |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| Mounting Method        | Recessed                      |
| Cut out (mm)           | 105                           |
| IP-rating              | IP20                          |
| Impact Protection (IK) | IK03 - 0.35 joule             |
| Operating Temperature  | -20 to +50                    |
| Housing                | PC (Polycarbonate)            |
| Colour of the Fixture  | White                         |
| Fixture Connection     | PI [Push-in connector 2-pole] |
| Product Serie          | DOWNLIGHT SLIM                |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 30  |
| Diameter (mm) | 118 |

**Sensor Information**  Guaranteed **budget prices**  Up to **7 years warranty**

Type of sensor



**Easy** return process

No Sensor



Long-life **LED solutions**